

# FPM-5151G FPM-5171G FPM-5191G

## 15" XGA/17" SXGA/19" SXGA Industrial Monitors with Resistive Touchscreens, Direct-VGA, and DVI Ports

**More Control Ltd**  
21 Drakes Mews  
Crownhill Industrial Estate  
Milton Keynes  
MK8 0ER  
Tel: 0345 00 00 400  
Fax: 0345 50 48 566  
Email: [sales@more-control.com](mailto:sales@more-control.com)  
Web: [www.more-control.com](http://www.more-control.com)



### Features

- 15" XGA or 17" / 19" SXGA TFT LED LCD with 50,000 backlight life time
- Direct VGA & DVI-D input interface
- Lockable OSD keys with 2 user-defined contrast/brightness settings
- Flat-sealed and IP65 certified front panel
- Robust design with anti-rust chassis and aluminum die-cast front panel
- Front accessible USB connector
- Combo RS-232 & USB interface for touchscreen function (optional)
- Supports industrial 10-30 V<sub>DC</sub> power input with Phoenix jack
- Supports panel, wall, desktop, rack or VESA arm mounting

### Introduction


The FPM-5000G series provides 15", 17" and 19" color TFT LCD with LED backlight flat panel monitors specifically designed for industrial applications. With a viewing size from 15" to 19", they present ample display areas as well as vivid and sharp images. It features Direct-VGA & DVI-D signal transmission, which allows VGA control cards to be used in your system. The onscreen display allows users to adjust the images on the screen with two user-defined settings. The front access USB connector provides easy access to the controller, and the industrial 10-30 V<sub>DC</sub> wide range power support makes this product an excellent option for Factory and Machine Automation display solutions.

### Specifications

General	
▪ <b>Button Controls</b>	OSD control pad on rear side with lockable function
▪ <b>Certification</b>	BSMI, CCC, CE, FCC Class A, UL
▪ <b>Dimensions (W x H x D)</b>	5151G: 449.92 x 315.63 x 50.5 mm (17.71" x 12.43" x 1.99") 5171G: 481.9 x 355.9 x 55 mm (18.97" x 14.01" x 2.17") 5191G: 481.93 x 384.6 x 59 mm (18.97" x 15.14" x 2.32")
▪ <b>Enclosure</b>	Front panel: Aluminum and flat-sealed Rear cover: Anti-rust coating
▪ <b>Mounting</b>	Panel, wall, desktop, VESA arm, or 19" rackmount
▪ <b>Power Input</b>	Phoenix Jack - 10 ~ 30 V <sub>DC</sub> input Optional external 57 W power adapter, with AC 100 V ~ 240 V input and DC +12 V @ 4.7A output
▪ <b>Power Consumption</b>	18 W + 20%/31 W + 20%/32 W + 20%
▪ <b>USB</b>	Front USB access for extension
▪ <b>Video Port</b>	VGA & DVI-D
▪ <b>Weight (Net)</b>	6 kg (13.22 lbs)/8 kg (17.63 lbs)/10 kg (22.04 lbs)
LCD Display	
▪ <b>Display Type</b>	XGA/SXGA/SXGA TFT LCDs
▪ <b>Display Size</b>	15"/17"/19"
▪ <b>Max. Resolution</b>	1024 x 768/1280 x 1024/1280 x 1024
▪ <b>Max. Color</b>	16.2M / 16.7M / 16.7M
▪ <b>Viewing Angle (H/V°)</b>	160/140, 170/160, 170/160
▪ <b>Luminance (cd/m²)</b>	400/350/350
▪ <b>Backlight Life (hrs)</b>	50,000
▪ <b>Contrast Ratio</b>	700:1 / 1000:1 / 1000:1
Touchscreen (Optional)	
▪ <b>Sensor</b>	AMT
▪ <b>Driver</b>	Penmount 6000
▪ <b>Type</b>	5-wire Resistive
▪ <b>Interface</b>	RS-232 & USB
▪ <b>Lifespan</b>	10/10/36 million with a silicone rubber of R8 finger, writing rate is by 250g at 2 times/s
▪ <b>Light Transmission</b>	> 80%
▪ <b>OS Support</b>	Windows XP,Vista,7,8,XPe,CE and Linux
▪ <b>Power Consumption</b>	+5 V @ 100 mA
▪ <b>Touch Resolution</b>	Linearity
Environment	
▪ <b>Operation Temperature</b>	0 ~ 50°C (32 ~ 122°F)
▪ <b>Storage Temperature</b>	-20 ~ 60°C (-4 ~ 140°F)
▪ <b>Humidity (Storage)</b>	10 ~ 90% non-condensing
▪ <b>Waterproof</b>	Front panel is IP65 compliant
▪ <b>Vibration</b>	5 ~ 500 Hz, 1 Grms (Operating, Random)
Ordering Information	
▪ <b>FPM-5191G-X0BE</b>	19" SXGA Ind. Monitor
▪ <b>FPM-5191G-R3BE</b>	19" SXGA Ind. Monitor w/Resistive TS(RS-232,USB)
▪ <b>FPM-5171G-X0BE</b>	17" SXGA Ind. Monitor
▪ <b>FPM-5171G-R3BE</b>	17" SXGA Ind. Monitor w/Resistive TS(RS-232,USB)
▪ <b>FPM-5151G-X0BE</b>	15" XGA Ind. Monitor
▪ <b>FPM-5151G-R3BE</b>	15" XGA Ind. Monitor w/Resistive TS(RS-232,USB)

## Dimensions

Unit: [mm]




**Panel Cut-out Dimensions:** FPM-5151G: 424 x 293 mm (16.69" x 11.54")  
 FPM-5171G: 454 x 338 mm (17.87" x 13.31")  
 FPM-5191G: 454 x 338 mm (17.87" x 13.31")

## Accessories


- **FPM-5151G-SMKE** FPM-5151G/5171G Stand Kit
- **FPM-5191G-SMKE** FPM-5191G Stand Kit
- **IPPC-6152A-RMKE** IPPC-6152A/FPM-5151G Rack Mount Kit
- **IPPC-6172A-RMKE** IPPC-6172A/FPM-5171G Rack Mount Kit
- **IPPC-6192A-RMKE** IPPC-6192A/FPM-5191G Rack Mount Kit
- **1702002600** Power Cable US Plug 1.8 M
- **1702002605** Power Cable EU Plug 1.8 M
- **1702031801** Power Cable UK Plug 1.8 M
- **1700000596** Power Cable China/Australia Plug 1.8 M
- **1757003822** ADAPTER 100-240V57W12V4.75A W/O PFC SPU63-105 L5

Note: VESA mounting screw length: M4 x 6mm

## I/O View



## Back View



## Front Accessible USB Port

